



Paint Protection Film Customer Care Sheet ©

We trust that you will enjoy your invisible paint protection product. It is designed to prevent the premature destruction of your automobile's delicate and valuable paintwork as well as the head/fog lights. Properly maintained, it has proven itself to be trouble free.

WHAT TO EXPECT IMMEDIATELY AFTER INSTALLATION:

- Immediately after installation, there may be a small amount of setting solution residue remaining under the film – **THIS IS NORMAL** and **IT WILL DISSIPATE** within a short time. **DO NOT** press on the area with the solution. Very similar to the temporary blemishes found on window tint application, these visual annoyances will clear up.
- Minor variations observed in the material itself will also clear up after time and exposure to the elements. Some cosmetic imperfections, often referred to as “disturbed adhesive”, are unavoidable and may make themselves evident as a result of the installation technique necessary to apply the film.
- Your film has been waxed with a special sealant prior to installation. No immediate waxing is required.

CARE (after 72 hours):

- You can wash your car as you would normally (hand washing is recommended). Take care to wash/dry parallel to the film edges.
- Wax the film at the same time as the rest of the car (every 3-4 months).
- The use of high-speed rotary buffers or other abrasive cleaning methods are **NOT** recommended for the film.
- Never apply pressure to a film protected surface.
- When waxing/polishing, **ALWAYS** overlap the film edge with a ¼” painters masking tape. This will prevent any wax build-up on the film edge.
- If the film becomes scratched or marred, reconditioning by a professional is recommended.